

LED Control Card and LED Display Module Shop
www.ledcontrolcard.com

Full color Asynchronous –Synchronous Play Controller
Led display controller HD-A60X Series----High Definition

Features:

1. Support Asynchronous and Synchronous using, plug and play.
2. Support 1080P,720P High Definition
3. Support 0-65536 gray scale.
4. Support U-disk expanding memory, also SD card expand
5. Support Digital Video Camera(DV) and Digital CATV Receiver ,no need Video processor
6. Support stereo audio output
7. Plug and play without any network settings.
8. Support network cluster management.



Parameter:

Type	Indoor & outdoor full-color & single/dual color module &Virtual module Support MBI5041/5042, MBI5050, MY9221, MY9268 etc and PWM
Scan mode	Support 1-32 scan randomly and static
Control range	HD-A601: Full color /Single dual color 800W*600H HD-A602: Full color /Single dual color 1280W*720H HD-A603: Full color /Single dual color 1280W*720H
Gray Scale	0-65536
Video format	AVI, WMV, MP4, 3GP, ASF, MPG, FLV, F4V, MKV, MOV, DAT, VOB, TRP, TS, WEBM, etc.
Image format	BMP, GIF, JPG, JPEG, PNG, GIF, PBM, PGM, PPM, XPM, XBM etc.
Text	Text and Image being edited directly. Document like Word, Excel, PPT, PPTX ;txt, rtf, html etc. can be edited as well after importing directly.
Time	Classic Analog clock, digital clock and various of clock with image background
Audio output	Double track stereo audio output
Memory	4G Flash; also offer 4G or 8G or 16G of SD card; Indefinite expanding of U-disk memory.
Communication	10/100M/1000M RJ45 Ethernet; 3G; Internet; LAN
Working Voltage	9/12V Adapter
Working Temperature	-20°C -80°C
	IN: 9V Power Adapter x1, 10/100M/1000M RJ45 x1, USB 2.0 x1, Micro USB X1, HDMI X1, CVBS

LED Control Card and LED Display Module Shop

www.ledcontrolcard.com

Port	X1, 3G lines x1, SD card x1, SIM card x1, power x1, Reset button x1, Testing button x1 OUT: 1000M RJ45 X2, Audio x1, HDMI X1
Software	HDPlayer